



HP Premium Gloss Air GR



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Intermediate polymeric adhesive vinyl with gray removable adhesive

See outstanding image quality and great hiding power

This gloss-finish, intermediate polymeric adhesive vinyl offers outstanding image quality and “pop”. The gray removable adhesive is opaque for maximum coverage. This vinyl installs easily with an air-release liner.

Gain efficiency while providing outstanding color fidelity

Save time and gain efficiency with ICC profiles that help you quickly get the color you need.

Save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Indoor and outdoor signage	Outstanding image quality on this intermediate calendared vinyl
	Point-of-sale, retail displays	Gray removable adhesive provides opacity to achieve consistent image quality on multiple surfaces
	Indoor and outdoor advertising	Air release liner enables fast and easy installation
	Window graphics	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks
	Exhibit and event displays	

Technical specifications



HP Premium Gloss Air GR

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks			
Liner	140 g/m ² double-sided PE air-release liner			
Thickness (base vinyl)	80 microns/3.15 mil per ISO 20534 Test Method			
Base vinyl	Polymeric calendered			
Adhesive	Gray, removable pressure-sensitive adhesive			
Opacity	>99% per TAPPI T-425 Test Method			
Finish	Gloss, >80 gloss units at 60° reflection			
Water resistance	Water resistant with HP 871 and 831 Latex Inks ¹			
Service temperature	-25 to 70° C (-13 to 158° F)			
Operating temperature	8 to 35° C (46 to 95° F)			
Storage temperature	5 to 25° C (41 to 77° F)			
Storage humidity	20 to 50% RH			
Lamination	Cold lamination; recommend using HP Everyday Matte or Gloss Laminate CP			
Shelf life	1 year, unopened in original packaging			
Environmental	REACH compliant ²			
Country of origin	Product of China			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	8T7U6A	1372 mm x 50 m (54 in x 164 ft)	848412027310	China, Vietnam, Thailand, Indonesia, and India
	8T7U7A	1372 mm x 100 m (54 in x 328 ft)	848412027327	China, Vietnam, Thailand, Indonesia, and India
	8T7U8A	1524 mm x 50 m (60 in x 164 ft)	848412027334	China, Vietnam, Thailand, Indonesia, and India
	8T7U9A	1524 mm x 100 m (60 in x 328 ft)	848412027341	China, Vietnam, Thailand, Indonesia, and India
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			

¹ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: HPLFMedia.com/hp/printpermanence.

² See the HP REACH Declaration published at [HP.Printing.Products.and.Consumable.Supplies](https://HPLFMedia.com/hp/en/contactus).

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

