

Item No.: FYE4I-2 Aqueous Matte Polyester Canvas

Application

Decorative Painting, Canvas, Exhibition Painting

Technical Specifications

Base Material	100%Polyester	DIN 60001,ASTM D7641
Yarn	600D*600D	DIN EN ISO 2060,ASTM D1907
Weave Method	Woven	---
Weight	285 ± 15gsm	ISO536
Thickness	390 ± 40 μ m	ISO534
Opacity	> 85%	ISO2471
Whiteness	140 ± 10	ISO11475
Color	L*: 92.0 ± 2.0; a*: 6.5 ± 2.0; b*: -13.5 ± 2.0	---
Flame Resistance	NO	---
Gloss[60°]	2-4	---
Anti-Scratch	NO	---

Size

Width	0.61 m/0.914 m/1.07 m/1.118 m/1.27 m/1.524 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	30 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.
It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH;
Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

