



HP Premium Gloss Air CR



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Intermediate polymeric adhesive vinyl with clear removable adhesive

Achieve vibrant print quality

Create high-impact signage with sharp, vibrant print quality while enjoying excellent value. Experience ease of installation with excellent lay-flat properties and an air-release liner.

Gain efficiency while providing outstanding color fidelity

Save time and gain efficiency with ICC profiles that help you get the color you need quickly—ideal for a wide range of indoor and outdoor applications.

Save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Indoor and outdoor signage	Outstanding image quality on this intermediate, polymeric calendared vinyl
	Point-of-sale, retail displays	Air release liner enables fast and easy installation
	Indoor and outdoor advertising	Print with ease using the complete HP solution—media, inks, profiles, printer
	Window graphics	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks
	Exhibit and event displays	

Technical specifications



HP Premium Gloss Air CR

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks
Liner	140 g/m ² double-sided PE air-release liner
Thickness (base vinyl)	80 microns/315 mil per ISO 20534 Test Method
Base vinyl	Calendered polymeric
Adhesive	Clear, removable pressure-sensitive adhesive
Opacity	>90% per TAPPI T-425 Test Method
Finish	Gloss, >80 gloss units at 60° reflection
Water resistance	Water resistant with HP 871 and 831 Latex Inks ¹
Service temperature	-25 to 70° C (-13 to 158° F)
Operating temperature	8 to 35° C (46 to 95° F)
Storage temperature	5 to 25° C (41 to 77° F)
Storage humidity	20 to 50% RH
Lamination	Cold lamination; recommend using HP Everyday Matte or Gloss Laminate CP
Shelf life	1 year, unopened in original packaging
Environmental	REACH compliant ²
Country of origin	Product of China

Ordering information	Product numbers	Roll sizes	UPC codes	Region
	8T7T8A	1372 mm x 50 m (54 in x 164 ft)	848412027273	China, Vietnam, Thailand, Indonesia, and India
	8T7T9A	1372 mm x 100 m (54 in x 328 ft)	848412027280	China, Vietnam, Thailand, Indonesia, and India
	8T7U0A	1524 mm x 50 m (60 in x 164 ft)	848412027297	China, Vietnam, Thailand, Indonesia, and India
	8T7U1A	1524 mm x 100 m (60 in x 328 ft)	848412027303	China, Vietnam, Thailand, Indonesia, and India

Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .
-----------------	--

¹ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: HPLFMedia.com/hp/printpermanence.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](https://HPLFMedia.com/hp/en/contactus).

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

